

Soil Wall-like, Siloxane Resin Based, Elastic Decorative Coating

SAND ELEGANTE

Formaldehyde Emission Class F☆☆☆☆

SAND ELEGANTE is a new type of decorative coatings. Combining the texture of natural soil, sand, stone and sea shells, SAND ELEGANTE provides totally new designs with touch of natural beauty.

Mixing the warm texture of earth, the fine texture of sand, and the rough texture of stone, SAND ELEGANTE creates a new type of design. Moreover, SAND ELEGANTE, imaging various walls in the world, enables a wide range of colours. Choose from a wide range of colours, such as traditional Japanese soil walls, bright pastel colours of Southern Europe, sand walls of dry regions, etc. and create your own style.



Feature

Excellent Design

Combining the texture of natural soil, sand and stone, SAND ELEGANTE provides natural designs.

Strong Weather Resistance

SAND ELEGANTE, containing siloxane resin, provides excellent weather resistance and high durability without topcoat.

Water Repellency

Coupled with elastic mid-coat, SAND ELEGANTE provides excellent water repellency. It covers hairline cracks on substrate and prevents rainwater from penetrating into substrate.

Mildew and Algae Resistance

With superior technology, SAND ELEGANTE achieves remarkable anti-germ and anti-algae performance and provides hygienic environment.

High Safety Level

Having water base property, SAND ELEGANTE is safe and environmentally friendly. Different from solvent type materials, it does not cause poisoning and fire.

Elastic Property

Elastic film of SAND ELEGANTE prevents hairline cracks of substrate, enhancing water resistance.

Pattern



Headquarter in Japan
SK Kaken Co., Ltd. 5-25, 3-Chome, Nakahozumi, Ibaraki-City, Osaka
567-0034, Japan
Tel: (81-72) 621 7727 Fax: (81-72) 621 7728

Hong Kong
SKK (HK) Co., Ltd. Suites 1007-1010, 10th Floor, Dah Sing Financial Centre, 108
Gloucester Road, Wanchai, Hong Kong
Tel: (852) 2529 3968 Fax: (852) 2527 0299

Singapore
SKK (S) Pte. Ltd. No.14, Pandan Road, Singapore 609262
Tel: (65) 6274 0020 Fax: (65) 6278 0060

Malaysia
SK Kaken (M) Sdn. Bhd. No.7, Jalan Sepadu 25/123, Seksyen 25, Taman Perindustrian
Axis, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: (60)3 5122 4800 Fax: (60)3 5122 4808

Thailand
SK Kaken (Thailand) Co., Ltd. 161/1 SG TOWER 5th Floor, Unit 504-505, Soi Mahadlek
Luang 3, Ratchadamri Road, Lumpinee, Pathumwan Bangkok 10330, Thailand
Tel: (66-2) 651 8722 Fax: (66-2) 651 8721

Website: <http://www.sk-kaken.co.jp>
<http://www.sk.com.hk>
<http://www.sk.com.sg>

Standard Colours (45 colours)



- Note : 1. Printed colours may be slightly different from actual material colours. We highly recommend you to check with sample board and/or catalogue for colour confirmation before placing orders.
 2. As only some standard colours are shown here, refer to catalogues of SAND ELEGANTE for other colours.

Standard Application

■ Rough Finish

(20°C, 65%RH)

Process	Material	Dilution ratio (wt. %)	Consumption (kg/m ²)	No.of coat	Interval (hrs)			Remarks	
					In process	In processes	Final curing		
1	SAND ELEGANTE UNDERCOAT	100	0.20 - 0.25	1 - 2	Over2	Over2	—	Wool roller Brush Spray	
	Water	5 - 15	—						
2	SAND ELEGANTE	100	2.5 - 3.0	1	—	(pressing with roller) within 5 minutes.	Over24	SK ALMIGHTY GUN Nozzle Tip:8-10mm Pressure:392-588kPa	
	Water	1 - 3	—						
(3)	※ 1, 2 Topcoat	CERAMI TOP Si	Pre-mixed	0.18 - 0.22	2	Over2	—	Over24	Wool roller, Brush, Airless spray gun Discharge : 800-1000ml/min. Pattern width : 25-30cm

※1. In case of applying topcoat, refer to the above (3).

※2. Ensure that all the surface is completely painted by CERAMI TOP Si without any area left unpainted.

* For other finishes, please contact to the nearest sales office.

● Uses

interior and exterior of houses, apartments, hotels, commercial buildings, etc.

● Available Substrates

concrete, cement rendering, PC panels, ALC panels, slate boards, siding boards, etc.

(Depending on the type of substrate, different primer is recommended. Contact the nearest SKK office for the details.)

● Packing

SAND ELEGANTE UNDERCOAT 16kg/can
 SAND ELEGANTE BASE 20kg/can

* In case substrate may be stained in renovation, apply SK STAIN SEALER W (15kg/can) prior to SAND ELEGANTE UNDERCOAT.

* For the packing style of CERAMI TOP Si, contact the nearest sales office for details.

Hazards Information and Safety Precautions

Read cautions written on containers thoroughly before use.
 Refer to MSDS(Material Safety Data Sheet) for the details.
 Pay close attention to the safety control when handling products.